



Top mounted Reach-In refrigerators

AGB Series

CHARACTERISTICS



Energy efficiency

Better energy class due to the optimized circulation of air, the use of **R-290 refrigerant** and electronic fans, for a **better interior temperature distribution**.



Lighting

LED lighting incorporated, **reducing** energy consumption **between 80% and 90%** compared to a traditional light bulb.



Certifications

Infrico is audited and certified by the international organization AENOR in **ISO 9001: 2015** (Quality); **ISO 14001: 2015** (Environment); **OSHAS 18001: 2007** (Worker Safety and Health) and by **INTERTEK** in accordance with **UL 471** and **NSF 7**.



Door lock

Compatible with 18" x 26" and 12" x 20" sheet pans



Compact monoblock system



Natural refrigerant R-290
GWP = 0



Expansion valve

More details and technical sheet



ETL LISTED TO UL471 standard and sanitation classified to NSF / We reserve the right to change specifications without prior notice. Non contractual pictures

MOD.



| | → | ↗ | ↑ | 🚪 | 🌀 | 🌡️ | 📦 | ⚙️ | ⚡ | 📏 | 💰 |
|-----------|--------------------|--------|---------|------|-------|-----------|------|-------|------|-----|----------|
| | Overall Dimensions | Doors | Shelves | (°F) | (ft³) | (HP) | 115V | [Lbs] | [\$] | | |
| IRR-AGB23 | 27 | 31-1/4 | 84 | 1 | 3 | 33°F/38°F | 23.0 | 1/4 | 3.8 | 380 | \$7.980 |
| IRR-AGB49 | 54-1/2 | 31-1/4 | 84 | 2 | 6 | 33°F/38°F | 49.0 | 1/3 | 4.0 | 700 | \$12.800 |

Height already includes 5-1/8" for casters

Top mounted Reach-In refrigerators

AGB Series

TECHNICAL CHARACTERISTICS



Refrigeration

Monoblock compact **refrigeration** system.

Hot gas defrost (BT).

Electronic fans.

Air cooled condensation system.

Forced air evaporation system.

Evaporative tray without electrical heater for a better energy consumption.



Doors

Doors with **integrated** dual sided **handle** and stay **open hinge**.

Four-chamber flat "seamless" snap-in door gasket easy to remove.

Field reversible doors [AGB23 hardware needed]



IRR-AG49

STANDARD FEATURES

| | | |
|---|--|--|
| REFRIGERATION | Expansion valve | Forced air refrigeration system |
| ELECTRICAL | Cord and NEMA 5-15P plug, electrical connection is 115V / 1ph / 60Hz | |
| DOE | Hydrocarbon R-290 | |
| AMBIENT | Temp 100°F | |
| OPTIONS Section 10 [Accessories & parts] | Stainless Steel wire shelves Stainless Steel tray divider | Additional slide kits Set of 6" legs, height adjustable from 5" to 8" |



Top mounted reach-In Solid door freezers

AGB Series

CHARACTERISTICS



Energy efficiency

Better energy class due to the optimized circulation of air, the use of **R-290 refrigerant** and electronic fans, for a **better interior temperature distribution**.



Lighting

LED lighting incorporated, **reducing** energy consumption **between 80% and 90%** compared to a traditional light bulb.



Certifications

Infrico is audited and certified by an international organization AENOR in **ISO 9001: 2015** (Quality); **ISO 14001: 2015** (Environment); **OSHAS 18001: 2007** (Worker Safety and Health) and by **INTERTEK** in accordance with **UL 471 and NSF 7**.



Non electric condensate pan

Full-height door opening
(22-7/8" x 58-5/8")

IRR-AGB23BT



Compact monoblock system



Natural refrigerant R-290
GWP = 0



Expansion valve

More details and technical sheet



MOD.

| | → | ↗ | ↑ | 🚪 | 🌀 | 🌡️ | 📦 | ⚙️ | ⚠️ [Amps] | 📏 [Lbs] | 💰 [\$] |
|--|--------------------|---|---|-------|---------|------|-------|------|-----------|---------|--------|
| | Overall Dimensions | | | Doors | Shelves | [°F] | [ft³] | [HP] | 115V | [Lbs] | [\$] |

| | | | | | | | | | | | |
|-------------|--------|--------|----|---|---|----------|------|--------|------|-----|----------|
| IRR-AGB23BT | 27 | 31-1/4 | 84 | 1 | 3 | -5°F/0°F | 23.0 | 3/4 | 7.2 | 375 | \$9.700 |
| IRR-AGB49BT | 54-1/2 | 31-1/4 | 84 | 2 | 6 | -5°F/0°F | 49.0 | 1 -1/4 | 10.5 | 620 | \$13.500 |

ETL LISTED TO UL471 standard and sanitation classified to NSF / We reserve the right to change specifications without prior notice. Non contractual pictures

Top mounted reach-In Solid door freezers

AGB Series

CHARACTERISTICS



Refrigeration

Monoblock compact **refrigeration** system.

Hot gas defrost [BT].

Electronic fans.

Air cooled condensation system.

Forced air evaporation system.

Evaporative tray without electrical heater for a better energy consumption.



Doors

Doors with **integrated** dual sided **handle** and stay **open hinge**.

Four-chamber flat "cleanless" snap-in door gasket easy to remove.

Field reversible doors [AGB23 hardware needed]

AISI 304 stainless steel



IRR-AGB49BT

STANDARD FEATURES

| | | |
|--|--|--|
| REFRIGERATION | Expansion valve and hot gas defrost system | |
| ELECTRICAL | Cord and NEMA 5-20P plug, electrical connection is 115V / 1ph / 60Hz Cord and NEMA 5-15P plug, [AGB 23BT] | |
| DOE | Hydrocarbon R-290 | |
| DOORS | Heated door frame to avoid accumulation of ice | |
| AMBIENT | Temp 100°F | |
| OPTIONS Section 10 [Accessories & parts] | Stainless Steel wire shelves Stainless Steel tray divider | Additional slide kits Set of 6" legs, height adjustable from 5" to 8" |



Top mounted reach-In Split glass door refrigerators

AGB Series

CHARACTERISTICS



Energy efficiency

Better energy class due to the optimized circulation of air, the use of **R-290 refrigerant** and electronic fans, for a **better interior temperature distribution**.



Lighting

LED lighting incorporated, **reducing** energetic consumption **between 80% and 90%** respect to a traditional light bulb.



Certifications

Infrico is audited and certified by an international organization AENOR in **ISO 9001: 2015** (Quality); **ISO 14001: 2015** (Environment); **OSHAS 18001: 2007** (Worker Safety and Health) and by **INTERTEK** in accordance with **UL 471 and NSF 7**.



IRR-AGB23CR



Compact monoblock system



Natural refrigerant R-290
GWP = 0



Expansion valve

More details and technical sheet



ETL LISTED TO UL471 standard and sanitation classified to NSF / We reserve the right to change specifications without prior notice. Non contractual pictures

MOD.

| | Overall Dimensions | | | Doors | Shelves | [°F] | [ft³] | [HP] | 115V | [Lbs] | [\$] |
|--|--------------------|--|--|-------|---------|------|-------|------|------|-------|------|

| | | | | | | | | | | | |
|-------------|--------|--------|----|---|---|-----------|------|-----|-----|-----|----------|
| IRR-AGB23CR | 27 | 31-1/4 | 84 | 1 | 4 | 33°F/38°F | 23.0 | 1/3 | 4,1 | 380 | \$8.400 |
| IRR-AGB49CR | 54-1/2 | 31-1/4 | 84 | 2 | 8 | 33°F/38°F | 49.0 | 1/3 | 4,1 | 620 | \$12.200 |



Top mounted reach-In Split glass door refrigerators

AGB Series

TECHNICAL CHARACTERISTICS



Refrigeration

Monoblock compact **refrigeration** system.

Hot gas defrost [BT].

Electronic fans.

Air cooled condensation system.

Forced air evaporation system.

Evaporative tray without electrical heater for a better energy class.



Doors

Doors with **integrated** dual sided **handle** and stay **open hinge**.

Four-chamber flat "cleanless" snap-in door gasket easy to remove.

Field reversible doors [AGB23 hardware needed]

Refrigeration
Air flow



IRR-AGB49CR



RGB LED lighting
[standard]

STANDARD FEATURES

| | | |
|---|--|--|
| ELECTRICAL | Cord and NEMA 5-15P plug, electrical connection is 115V / 1ph / 60Hz | |
| DOE | Hydrocarbon R-290 | |
| SHELVING | Plastic coated reinforced wire shelves hold up 155 lb | |
| DOORS | Door built-in Thermopane double glass [Refrigerators models] | |
| OPTIONS Section 10 [Accessories & parts] | Stainless Steel wire shelves Stainless Steel tray divider | Additional slide kits Set of 6" legs, height adjustable from 5" to 8" |