

7. DISPLAY CASES

PASTRY DISPLAY CASES STRAIGHT GLASS

ETL LISTED TO UL 471 standard and sanitation classified to NSF / We reserve the right to change specifications without prior notice. In contractual purchase

7



VBR FG SERIES



**EACH SHELF
HOLDS UP TO
45 LBS**

DISPLAY CASES

7. DISPLAY CASES

PASTRY DISPLAY CASES STRAIGHT GLASS



ETL LISTED TO UL 471 standard and sanitation classified to NSF / We reserve the right to change specifications without prior notice. Non contractual pictures

7

MODELS	→	↗	↑	📱	🌡️	📦	⚙️	⚡	📏	💰
	Overall Dimensions			Doors	(°F)	(ft³)	(HP)	(Amps) 115V	(Lbs)	(\$)
IDC-VBR9FG	38-1/4	31-7/8	51-1/8	2	39°F/45°F	10.0	1/2	7.8	489	\$13,050
IDC-VBR12FG	50-1/2	31-7/8	51-1/8	2	39°F/45°F	13.0	3/4	7.9	635	\$14,900
IDC-VBR18FG	75-1/8	31-7/8	51-1/8	3	39°F/45°F	20.0	1	8.8	950	\$18,800

VBR FG SERIES



**EACH SHELF
HOLDS UP TO
45 LBS**

- AISI 304 Stainless steel, including stainless top,
- Heavy duty ball bearing and levelling feet,
- Glass sided panels with thermopane double glass.
- Tempered flat glass front & top panel.
- LED lighting in canopy and under each glass shelf,
- Glass shelves built into silver anodized Aluminum frames, easy removable for cleaning.
- Rear sliding doors.
- Digital temperature controller with automatic defrost system,

- Forced air refrigeration system,
- Cord and NEMA 5-20P plug,
- Electrical connection is 115V / 1ph / 60Hz.
- Dry case. Please consult for \$.
- This product is designed to operate at the following store conditions 75°F and 55% R.H.
- This display refrigerator is not for the display of potentially hazardous foods.