

AGN SERIES | REACH-IN FOR A SMALL FOOTPRINT

SLIM LINE SOLID & GLASS DOOR



5 YEAR WARRANTY
Parts & Labor - 7 YEARS COMPRESSOR



RGB LED lighting
(option)



   InfricoUSA

Infrico

USA

INFRICO USA CORP
11200 NW 25th Street STE 123
Sweetwater, FL 33172
305-777-9599
sales@infrico.com



AGN SERIES | REACH-IN FOR A SMALL FOOTPRINT



SPECIFICATIONS

EXTERIOR

- AISI 304 Stainless steel.

INTERIOR

- AISI 304 Stainless steel.
- Sealed interior floors and rounded cabinet corners.
- Led lighting.
- Internal drain plug for easy cleaning.

SHELVING

- Three plastic coated (four for CR models) wire shelves per door with stainless steel tray slides included.
- Plastic coated tray divider (CR models).

DOORS

- Polyurethane insulated doors.
- Self closing doors with stay open feature.
- Stainless steel heavy-duty hinges.
- Triple chamber snap in door gaskets for easy removal and cleaning.
- Doors locks.
- Full-height door opening (22-7/8" x 58-5/8").

ELECTRICAL

- Cord and NEMA 5-15P plug, electrical connections is 115V / 1ph / 60Hz
- Cord and NEMA 5-15P plug, (AGB 23BT)

STANDARD FEATURES

REFRIGERATION

- Forced air refrigeration system.
- Digital temperature controller with automatic defrost system.
- Energy-saving non-electric condensate pan.
- Evaporator coil coated with anticorrosion material 100% Polyester -100°F ambient.
- Electronic fans.
- Hot gas defrost for low temp units.
- Forced air refrigeration and Capillary system
- Each compartments has its own refrigeration system (MX)
- Expansion valve (all) and hot gas defrost system (BT)

DOE DOORS

- BT Models: Heated door frame to avoid accumulation of ice
- Door built-in Thermopile double glass (CR Models)

OPTIONS

- Stainless Steel wire shelves
- Stainless Steel tray divider
- Additional slide kits
- Set of 6" legs, height adjustable from 5" to 8"

Model	Overall Dimensions			Doors	Shelves	(°F)	(ft3)	(HP)	115V	[Lbs]	DOE
IRR-AGN300CR	19	27-7/8	82-1/16	1	4	36/43 °F	11,5	1/3	4,3	269	
IRR-AGN301	19	27-7/8	82-1/16	1	3	33/38 °F	11,5	1/3	4,1	265	
IRR-AGN302	19	27-7/8	82-1/16	2	3	33/38 °F	11,5	1/3	4,1	265	
IRR-AGN301BT	19	27-7/8	82-1/16	1	3	0 °F	11,5	3/8	5,6	265	
IRR-AGN600CR	38-3/8	27-7/8	82-1/16	2	8	36/43 °F	26,30	3/8	5,8	392	Hydrocarbon R-290
IRR-AGN602	38-3/8	27-7/8	82-1/16	2	6	33 /38 °F	26,30	3/8	5,6	320	
IRR-AGN603	38-3/8	27-7/8	82-1/16	3	6	33 /38 °F	26,30	3/8	5,6	320	
IRR-AGN604	38-3/8	27-7/8	82-1/16	4	6	33 /38 °F	26,30	3/8	5,6	320	
IRR-AGN602BT	38-3/8	27-7/8	82-1/16	2	6	0 °F	26,30	3/4	8,5	320	
IRR-AGN602MX	38-3/8	27-7/8	82-1/16	2	6	33 / 38 °F 0 °F	11,5/26,30	1/3 - 3/8	8,08	392	