

MODEL: IBC-ABT101L
Blast Chillers and Shock Freezers – 10 Trays
General Strengths

- ✓ **Blast Chiller Functions.** Blast chillers and freezers, quickly reduce the core temperature of the products, whether they are cooked or fresh, conserving their fresh texture, hygiene and quality, while reducing the risk of bacteria generating.
- ✓ **Sanitation.** The interior cabinet is built with rounded corners (extensive radius for easy cleaning). Easy removal of shelves and slides for interior cleaning. Each cabinet has a drain at the bottom of the unit. When cleaning the unit make sure the drain hose is routed to a floor drain.
- ✓ **Doors.** Self-closing door system with permanent pressure. Stay open feature included when door remains open after 95 degrees. All doors include triple chamber door gaskets, easy to remove and snap in.
- ✓ **Control systems.** Greater ability for the adjustment of temperature ranges as per the end user's requirements.
- ✓ **100% Tested.** All condenser units are 100% tested, in helium chambers for refrigerant leak detections.
- ✓ **Certified.** Audited and Certified by INTERTEK for compliance with UL 471 and NSF 7. AENOR audited and certified by internationally recognized firm. ISO 9001:2015 (Quality); ISO 14001:2015 (Environmental); OSHAS 18001:2007 (Prevention and Worker Safety).



MODEL	Dimensions (inches) (mm)			Nº Doors	Nº Trays	Ref.	Ref. Weight (Lbs.) (gr.)	Temp. Range (°F) (°C)	Capacity Chiling/Freezing (Lbs.) (Kg)	Cond. Unit. H.P.	Case Amps	Crated Weight (Lbs.) (Kg.)
	W	D	H									
IBC-ABT101L	33	34-1/8	68-1/2	1	10	R404A	2.64	-40°F -40°C	88/55 40/25	2	5 (115V) 17 (230V)	600 272
	837	866	1740									



ETL LISTED TO UL471 STANDARD AND SANITATION CLASSIFIED TO NSF7 – WE RESERVE THE RIGHT TO CHANGE SPECIFICATIONS WITHOUT PRIOR NOTICE

MODEL: IBC-ABT101L

Blast Chillers and Shock Freezers – 10 Trays


STANDARD FEATURES

- **Compatible with any oven.**
- **Exterior**
 - AISI 304 Stainless Steel,
 - Compliant with HACCP regulations.
- **Interior**
 - AISI 304 Stainless Steel,
 - Sealed interior floors and rounded cabinet corners,
 - Internal drain plugs for easy cleaning.
 - Includes a heated conical probe which is easy to use and remove.
- **Insulation**
 - CFC-Free polyurethane insulation, entire cabinet structure is foamed-in using a high-density polyurethane insulation,
 - Low GWP & Zero ODP effect.
- **Doors**
 - Polyurethane insulated door,
 - Self-closing door with stay open feature,
 - Stainless Steel heavy-duty hinges,
 - Triple chamber snap in door gaskets for easy removal and cleaning,
 - Heated door frame to avoid accumulation of ice.
- **Trays**
 - (10) Stainless Steel trays.
 - Dimensions WxD: 23-5/8"x15-3/4" (600x400 mm),
 - Compatible with 18"x26" (457x660 mm) sheet pans.
- **Casters**
 - 4" diameter casters,
 - Locks provided on front set.

- **Refrigeration**
 - Control panel with an easy to read screen and menu,
 - Manual defrost during cycles and automatic defrost during maintenance,
 - Evaporator coil coated with anti-corrosion material 100% polyester,
 - Forced air refrigeration system,
 - Drain through plastic tray,
 - Refrigeration capacity: 7404 Btu/h(-13°F)/2170 W(-25°C),
 - **Blast chilling:** +194°F (+90°C) to +37°F (3°C) in less than 90 minutes,
 - **Blast freezing:** +194°F (+90°C) to 0°F (-18°C) in less than 4 hours.
- **Digital Control**
 - Interactive control screen & menu,
 - Up to 99 different customized cycles,
 - USB Connection. 
- **Electrical**
 - Cord and NEMA L14-30P plug. Electrical connections are 230V / 1ph / 60 Hz (compressor) and 115V / 1ph / 60 Hz (digital control). 
 - Must be connected to 40 Amp. circuit breaker!

➤ **ETL Listed to UL471 Standard and Sanitation classified to NSF7.**

PLAN VIEW



OPTIONAL FEATURES

- ✓ Set of 6" legs, height adjustable from 5" to 8",
- ✓ Electrical connection is: 230 V / 1ph / 50 Hz (plug type varies).

ETL LISTED TO UL471 STANDARD AND SANITATION CLASSIFIED TO NSF7 – WE RESERVE THE RIGHT TO CHANGE SPECIFICATIONS WITHOUT PRIOR NOTICE