

Project: _____
 Location: _____
 Item #: _____ Quantity: _____
 Model #: _____

**MODEL: IMD-ERV15IIGD / IMD-ERV25IIGD
 IMD-ERV35IIGD**

BOTTLES COOLER: BLACK FINISH GLASS DOOR



General Strengths

- ✓ **Sanitation.** Quick ability to take off shelves and slides for interior cleaning.
- ✓ **Doors.** All doors include door gaskets, easy to remove and snap in.
- ✓ **Control systems.** Higher precision in managing temperature settings. Greater ability for the adjustment of temperatures ranges as per the end user's requirement.
- ✓ **100% Tested.** All condenser units are tested 100%, in helium chambers for refrigerant leak detections.
- ✓ **Certified.** Audited and Certified by **INTERTEK** for compliance with UL 471 and NSF 7. EQA audited and certified by internationally recognized firm. ISO 9001:2015 (Quality); ISO 14001:2015 (Environmental); ISO 45001:2018 (Prevention and Worker Safety)
- ✓ **Lighting.** LED lighting in cabinet sides reduces the energy consumption by 80% and 90% compared to a traditional bulb. Provides a much better light quality.



Review:03 Date: 11/02/2023 IMD-ERV15_25_35_GD

EFL LISTED TO UL471 STANDARD AND SANITATION CLASSIFIED TO NSF7 – WE RESERVE THE RIGHT TO CHANGE SPECIFICATIONS WITHOUT PRIOR NOTICE

**MODEL: IMD-ERV15IIGD / IMD-ERV25IIGD
 IMD-ERV35IIGD**

BOTTLES COOLER: BLACK FINISH GLASS DOOR

STANDARD FEATURES

➤ **Exterior**

- AISI 430 Stainless Steel.
- Completely injected compact structure.
- Door lock.

➤ **Interior**

- Interior grey plastic-coated steel.
- LED lighting.

➤ **Doors**

- Double pane glass door.
- Triple chamber snap in door seals for easy removal.
- Black plastic handle included on the door.

OPTIONAL FEATURES

- ✓ Set of 2" Casters, front locking
- ✓ Electrical connection is 220-230 V / 1ph / 50Hz (plug type varies).
- ✓ Electrical connection is 220-230 V / 1ph / 60Hz (plug type varies).

➤ **Insulation**

- Polyurethane with high density 40kg/m³, CFSs free, zero ODP and low GWP.

➤ **Shelving**

- IMD-ERV15IIGD - (2) interior shelves.
- IMD-ERV25IIGD - (4) interior shelves.
- IMD-ERV35IIGD - (6) interior shelves.
- Guides and shelves easy to take off for cleaning.

➤ **Refrigeration**

- Temperature and defrost regulated by a digital controller.
- Forced air evaporation system.
- Forced air condensation system.
- Evaporative pan.
- Evaporator coil coated with anti-corrosion material.
- Refrigeration capacity:
 IMD-ERV15IIGD - 1512 Btu/h (14°F) / 443W (-10°C)
 IMD-ERV25IIGD - 1512 Btu/h (14°F) / 443W (-10°C)
 IMD-ERV35IIGD - 1512 Btu/h (14°F) / 443W (-10°C)

➤ **Electrical**

- Cord and NEMA 5-15P plug,
- Electrical connection is 115 V / 1ph / 60 Hz.



